

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	88	90	92	94
Total Lumens, 4' rail length (1219mm)	2686	2771	2827	2884
Lumens per foot (305mm)	672	693	707	721
Lumens per foot UP (305mm)	444	458	467	476
Lumens per foot DOWN (305mm)	228	235	240	245
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 80 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	110	113
Total Lumens, 4' rail length (1219mm)	5372	5542	5655	5768
Lumens per foot (305mm)	1343	1385	1414	1442
Lumens per foot UP (305mm)	887	915	934	952
Lumens per foot DOWN (305mm)	456	470	480	490
Input Power (W), 4' rail length (1219mm)	51.5	51.5	51.5	51.5
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 80 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	96	99	101	103
Total Lumens, 4' rail length (1219mm)	10207	10530	10744	10959
Lumens per foot (305mm)	2552	2632	2686	2740
Lumens per foot UP (305mm)	1685	1739	1774	1719
Lumens per foot DOWN (305mm)	867	894	912	884
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	76	78	80	81
Total Lumens, 4' rail length (1219mm)	2316	2389	2437	2486
Lumens per foot (305mm)	579	597	609	622
Lumens per foot UP (305mm)	382	394	402	411
Lumens per foot DOWN (305mm)	197	203	207	211
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	91	93	95	97
Total Lumens, 4' rail length (1219mm)	4631	4777	4875	4972
Lumens per foot (305mm)	1158	1194	1219	1243
Lumens per foot UP (305mm)	765	789	805	821
Lumens per foot DOWN (305mm)	393	406	414	422
Input Power (W), 4' rail length (1219mm)	51.5	51.5	51.5	51.5
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric, up | 40° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U1S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	83	85	87	89
Total Lumens, 4' rail length (1219mm)	8799	9077	9262	9448
Lumens per foot (305mm)	2200	2269	2316	2362
Lumens per foot UP (305mm)	1453	1499	1529	1482
Lumens per foot DOWN (305mm)	747	771	786	762
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.