

IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 80 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-35-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	87	90	92	93
Total Lumens, 4' rail length (1219mm)	2668	2752	2809	2865
Lumens per foot (305mm)	667	688	702	716
Lumens per foot UP (305mm)	441	455	464	473
Lumens per foot DOWN (305mm)	226	233	238	243
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.





IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 80 CRI | SO
 707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-35-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	105	108	110	112
Total Lumens, 4' rail length (1219mm)	5336	5505	5617	5730
Lumens per foot (305mm)	1334	1376	1404	1432
Lumens per foot UP (305mm)	882	910	928	947
Lumens per foot DOWN (305mm)	452	466	476	485
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).





IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 80 CRI | HO
 707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-35-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	95	98	100	102
Total Lumens, 4' rail length (1219mm)	10139	10459	10673	10886
Lumens per foot (305mm)	2535	2615	2668	2722
Lumens per foot UP (305mm)	1676	1729	1764	1709
Lumens per foot DOWN (305mm)	859	886	904	876
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI	85	85	85	85

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 90 CRI | LO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-LO-359-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	75	78	79	82
Total Lumens, 4' rail length (1219mm)	2300	2373	2421	2470
Lumens per foot (305mm)	575	593	605	617
Lumens per foot UP (305mm)	380	392	400	408
Lumens per foot DOWN (305mm)	195	201	205	209
Input Power (W), 4' rail length (1219mm)	30.8	30.8	30.8	30.8
Watts per foot (305mm)	7.8	7.8	7.8	7.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report



ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 90 CRI | SO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-SO-359-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	90	93	95	99
Total Lumens, 4' rail length (1219mm)	4600	4746	4843	4939
Lumens per foot (305mm)	1150	1186	1211	1235
Lumens per foot UP (305mm)	760	784	800	816
Lumens per foot DOWN (305mm)	390	402	410	419
Input Power (W), 4' rail length (1219mm)	51.3	51.3	51.3	51.3
Watts per foot (305mm)	12.9	12.9	12.9	12.9
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.



IES Report

ZipThree® | Ceiling Cable | 707 | Symmetric with EdgeGlow, up | 40° Symmetric, down | 90 CRI | HO

707-Z3-XX-4-48-CC-XX-XX-XX-X-0-Z-HO-359-U2S1-0-AL / WH-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	82	85	86	89
Total Lumens, 4' rail length (1219mm)	8741	9017	9201	9385
Lumens per foot (305mm)	2185	2254	2300	2346
Lumens per foot UP (305mm)	1445	1490	1521	1473
Lumens per foot DOWN (305mm)	741	764	780	755
Input Power (W), 4' rail length (1219mm)	107.2	107.2	107.2	107.2
Watts per foot (305mm)	26.8	26.8	26.8	26.8
CRI*	96	96	96	96

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on vode.com.