

IES Report

BoxRail® | 107 | White Baffle | 80 CRI | HO

107-BX-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-WB-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	44	45	46	46
Total Lumens, 4' rail length (1219mm)	2126	2193	2238	2238
Lumens per foot (305mm)	531	548	559	559
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES INDOOR REPORT

PHOTOMETRIC FILENAME : VODE_107_BX_HO_35_WB.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L121911507 (SOURCE REPORT FOR REFERENCE)
[TESTLAB] REPORT BASED ON DATA FROM NVLAP ACCREDITED LAB
[ISSUE DATE] 12/23/2019
[MANUFAC] Vode Lighting
[LUMCAT] 107-BX-48-Z-HO-35-WB-AL
[LUMINAIRE] BoxRail LED, 48", 3500K, 80 CRI, zipper board, white baffle,
[MORE] high output, clear anodized finish
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3565
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	73
Total Luminaire Watts	49.06
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	0.80
Spacing Criterion (Diagonal)	1.00
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.07 ft
Luminous Width (90-270)	3.84 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	19044	34479	26139
55	17340	22250	20716
65	18327	16453	16869
75	9522	10202	11902
85	6059	5049	5049

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_HO_35_WB.IES

CANDELA TABULATION

	<u>0</u>	<u>5</u>	<u>10</u>	<u>15</u>	<u>20</u>	<u>25</u>	<u>30</u>	<u>35</u>	<u>40</u>	<u>45</u>
0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0
5	2688.4	2686.2	2684.0	2679.6	2677.4	2670.8	2664.2	2657.6	2653.2	2648.8
10	2662.0	2659.8	2646.6	2633.4	2620.2	2611.4	2596.0	2576.2	2556.4	2530.0
15	2615.8	2607.0	2587.2	2567.4	2543.2	2505.8	2457.4	2409.0	2358.4	2310.0
20	2543.2	2527.8	2503.6	2470.6	2413.4	2340.8	2268.2	2197.8	2134.0	2083.4
25	2439.8	2417.8	2387.0	2323.2	2235.2	2142.8	2057.0	1991.0	1922.8	1837.0
30	2323.2	2299.0	2248.4	2151.6	2039.4	1933.8	1856.8	1742.4	1623.6	1513.6
35	2171.4	2142.8	2068.0	1951.4	1832.6	1738.0	1599.4	1454.2	1328.8	1223.2
40	1434.4	1438.8	1452.0	1471.8	1491.6	1414.6	1295.8	1172.6	1014.2	858.0
45	336.6	352.0	387.2	433.4	510.4	640.2	743.6	748.0	668.8	609.4
50	259.6	268.4	283.8	301.4	323.4	352.0	387.2	420.2	437.8	446.6
55	248.6	253.0	261.8	270.6	283.8	299.2	314.6	316.8	316.8	319.0
60	231.0	233.2	231.0	231.0	231.0	235.4	237.6	237.6	237.6	237.6
65	193.6	191.4	184.8	178.2	173.8	171.6	171.6	171.6	171.6	173.8
70	121.0	118.8	118.8	114.4	112.2	110.0	110.0	112.2	112.2	114.4
75	61.6	61.6	61.6	59.4	59.4	59.4	61.6	61.6	63.8	66.0
80	30.8	30.8	28.6	28.6	28.6	28.6	28.6	28.6	28.6	30.8
85	13.2	13.2	13.2	13.2	13.2	13.2	13.2	13.2	11.0	11.0
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Vert. Angles **Horizontal Angles**

	<u>50</u>	<u>55</u>	<u>60</u>	<u>65</u>	<u>70</u>	<u>75</u>	<u>80</u>	<u>85</u>	<u>90</u>
0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0	2695.0
5	2644.4	2642.2	2640.0	2637.8	2633.4	2633.4	2631.2	2629.0	2629.0
10	2505.8	2483.8	2461.8	2442.0	2426.6	2413.4	2404.6	2398.0	2395.8
15	2268.2	2228.6	2195.6	2167.0	2147.2	2129.6	2118.6	2114.2	2112.0
20	2039.4	1995.4	1947.0	1896.4	1856.8	1821.6	1797.4	1782.0	1777.6
25	1746.8	1665.4	1595.0	1533.4	1489.4	1454.2	1430.0	1416.8	1412.4
30	1421.2	1350.8	1276.0	1194.6	1124.2	1069.2	1031.8	1007.6	1001.0
35	1093.4	974.6	875.6	803.0	756.8	728.2	710.6	699.6	695.2
40	745.8	682.0	644.6	620.4	600.6	585.2	576.4	569.8	567.6
45	572.0	543.4	521.4	501.6	488.4	477.4	468.6	464.2	462.0
50	442.2	426.8	413.6	400.4	391.6	382.8	378.4	374.0	371.8
55	323.4	323.4	319.0	314.6	310.2	303.6	301.4	299.2	297.0
60	239.8	239.8	239.8	239.8	239.8	237.6	235.4	235.4	233.2
65	173.8	176.0	178.2	178.2	178.2	180.4	178.2	178.2	178.2
70	116.6	118.8	121.0	123.2	123.2	125.4	125.4	125.4	125.4
75	68.2	70.4	72.6	74.8	77.0	77.0	79.2	79.2	77.0
80	30.8	33.0	35.2	35.2	37.4	37.4	39.6	39.6	37.4
85	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_HO_35_WB.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	905.63	N.A.	25.40
0-30	1760.75	N.A.	49.40
0-40	2566.31	N.A.	72.00
0-60	3299.19	N.A.	92.50
0-80	3550.07	N.A.	99.60
0-90	3565.38	N.A.	100.00
10-90	3316.08	N.A.	93.00
20-40	1660.68	N.A.	46.60
20-50	2122.82	N.A.	59.50
40-70	908.30	N.A.	25.50
60-80	250.88	N.A.	7.00
70-80	75.46	N.A.	2.10
80-90	15.32	N.A.	0.40
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	3565.38	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	249.30
10-20	656.32
20-30	855.12
30-40	805.56
40-50	462.14
50-60	270.74
60-70	175.42
70-80	75.46
80-90	15.32
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : VODE_107_BX_HO_35_WB.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	97	98	96	94	95	93	92	90
2	104	98	93	89	102	96	92	88	93	89	86	90	87	84	87	84	82	80
3	97	89	83	78	95	88	82	77	85	80	76	82	78	75	80	77	74	72
4	91	82	75	69	89	80	74	69	78	72	68	76	71	67	74	70	66	65
5	85	75	68	62	83	74	67	62	72	66	61	70	65	61	68	64	60	59
6	80	69	62	57	78	68	61	56	67	60	56	65	60	55	64	59	55	53
7	75	64	57	52	74	63	56	51	62	56	51	60	55	51	59	54	50	49
8	71	59	52	47	69	59	52	47	58	51	47	56	51	47	55	50	47	45
9	67	55	48	44	66	55	48	44	54	48	43	53	47	43	52	47	43	42
10	63	52	45	41	62	51	45	40	50	44	40	50	44	40	49	44	40	39

POLAR GRAPH



Maximum Candela = 2695 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)