

IES Report



RaceRail® | 107 | Diffuse, round | 80 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-35-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	126	130	132	132
Total Lumens, 4' rail length (1219mm)	1730	1784	1821	1821
Lumens per foot (305mm)	432	446	455	455
Input Power (W), 4' rail length (1219mm)	13.8	13.8	13.8	13.8
Watts per foot (305mm)	3.5	3.5	3.5	3.5
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 80 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-35-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	145	150	153	153
Total Lumens, 4' rail length (1219mm)	3459	3568	3641	3641
Lumens per foot (305mm)	865	892	910	910
Input Power (W), 4' rail length (1219mm)	23.9	23.9	23.9	23.9
Watts per foot (305mm)	6.0	6.0	6.0	6.0
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 80 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-35-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	134	139	142	142
Total Lumens, 4' rail length (1219mm)	6572	6780	6918	6918
Lumens per foot (305mm)	1643	1695	1730	1730
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	82	82	82	82

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 90 CRI | LO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-LO-359-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	109	112	114	115
Total Lumens, 4' rail length (1219mm)	1491	1538	1570	1585
Lumens per foot (305mm)	373	385	392	396
Input Power (W), 4' rail length (1219mm)	13.8	13.8	13.8	13.8
Watts per foot (305mm)	3.5	3.5	3.5	3.5
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report



RaceRail® | 107 | Diffuse, round | 90 CRI | SO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-SO-359-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	125	129	132	133
Total Lumens, 4' rail length (1219mm)	2982	3076	3139	3170
Lumens per foot (305mm)	746	769	785	793
Input Power (W), 4' rail length (1219mm)	24.0	24.0	24.0	24.0
Watts per foot (305mm)	6.0	6.0	6.0	6.0
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).



IES Report

RaceRail® | 107 | Diffuse, round | 90 CRI | HO

107-RR-XX-4-48-XX-XX-XX-XX-X-X-Z-HO-359-2-X-XX-X

	2700K	3000K	3500K	4000K
Efficacy - Lumens per Watt	116	120	122	123
Total Lumens, 4' rail length (1219mm)	5666	5845	5964	6024
Lumens per foot (305mm)	1416	1461	1491	1506
Input Power (W), 4' rail length (1219mm)	49.1	49.1	49.1	49.1
Watts per foot (305mm)	12.3	12.3	12.3	12.3
CRI	94	94	94	94

Due to the large number of options in Vode's product offering, most Vode IES reports are factored reports prepared from source reports. Source reports are the IES test reports prepared for Vode by an NVLAP accredited photometric test laboratory. Factored reports are based on data from the Vode source reports.

If the data above is in black, it is directly from a Vode source report. If it is in grey, it is factored from Vode source reports. Reference details on Vode source reports can be found on the [IES File Finder](#) page on [vode.com](#).