



Spec Guide

# WingRail | Ceiling-Wall Arm | 107



Direct or indirect lighting for wall wash, grazing and ceiling wash applications.



WingRail: direct or indirect, 370° rotation.

### Benefits & Features

#### Minimal Profile, Robust Design

Asymmetric profile, 1.14 in x 2.12 in.

#### Superior Light Quality & Performance


Output up to 1376 lm/ft (HO), 121 lm/W (HO). 90 CRI static & tunable white 2200K - 5000K. Custom ranges available upon request.

#### High Performance Optics

Break through Batwing lens designed for excellent fixture to fixture spacing.

#### Better Optics & Beam Control Options

Asymmetric distribution. White or black Baffle, EdgeSoft™ lens, or diffuse lens and narrow optics available. Directional control with 360° rotation, angle gauge, and lock.



Integral Power



Double Rail with Tee, Small Square Canopy

Build Your Specification

| 107-WG             |                                  |                                                            |                                    |                                                        |                                                                                                          |                                               |
|--------------------|----------------------------------|------------------------------------------------------------|------------------------------------|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>System Code</b> | <b>Rail Type</b>                 | <b>Single/Double Rail</b>                                  | <b>System Length</b>               | <b>Rail Length</b>                                     | <b>Mounting</b>                                                                                          | <b>Arm Length</b>                             |
| 107 System   107   | <b>Singular Rail</b>             | <b>01</b> Single Rail                                      | Specify overall                    | <b>24</b> 24" (610mm)                                  | <b>CA</b> Ceiling Arm                                                                                    | <b>1.25</b> 1.25" arm (32mm) <sup>1</sup>     |
|                    | <b>WG</b> WingRail               | <b>03</b> Double Rail with 3" (76mm) Tee                   | system length                      | <b>36</b> 36" (914mm)                                  | <b>WA</b> Wall Arm                                                                                       | <b>3</b> 3" arm (76mm)                        |
|                    |                                  | <b>06</b> Double Rail with 6" (152mm) Tee                  | in ft/in or M/mm.                  | <b>48</b> 48" (1219mm)                                 |                                                                                                          | <b>6</b> 6" arm (152mm)                       |
|                    | <b>Dual Hub</b> <sup>9</sup>     | <b>12</b> Double Rail with 12" (305mm) Tee                 |                                    | <b>60</b> 60" (1524mm)                                 |                                                                                                          | <b>12</b> 12" arm (305mm)                     |
|                    | <b>2W</b> WingRail - WingRail    | <b>DH</b> Double Rail with Dual Hub                        | <i>Corner and Shapes available</i> | <b>72</b> 72" (1829mm)                                 |                                                                                                          | <b>18</b> 18" arm (457mm) <sup>2</sup>        |
|                    | <b>ZZ</b> Other (please specify) | <b>DH03</b> Double Rail with Dual Hub with 3" (76mm) Tee   | <i>See Guide</i>                   | <b>ZZ</b> Other rail length or layout (please specify) |                                                                                                          | <b>24</b> 24" arm (610mm) <sup>2</sup>        |
|                    |                                  | <b>DH06</b> Double Rail with Dual Hub with 6" (152mm) Tee  | <i>or details.</i>                 |                                                        |                                                                                                          | <b>ZZ</b> Other (please specify) <sup>2</sup> |
|                    |                                  | <b>DH12</b> Double Rail with Dual Hub with 12" (305mm) Tee |                                    |                                                        | See <b>Rail Length Chart</b> for more details.                                                           |                                               |
|                    |                                  | <b>ZZ</b> Other (please specify)                           |                                    |                                                        | <b>▲ Custom lengths may result in light gaps on the fixture. See Rail Length Chart for more details.</b> |                                               |

| Power Location                                                                      | Power Type                                                                                   | Voltage                    |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|----------------------------|
| <b>Integral Power</b>                                                               | <b>Flexible 1 to 1 Power</b>                                                                 | <b>1</b> 120V              |
| <b>IP</b> Integral Power                                                            | <b>AE</b> 0-10V, 1.0% Dimming                                                                | <b>2</b> 120V - 277V       |
| <b>Remote Power</b>                                                                 | <b>AT</b> 0-10V, 0.1% Dimming                                                                | <b>X</b> Not Yet Specified |
| Specify mounting and harness length code example: <b>2R25</b> , <b>4R25</b> ...etc. | <b>AD</b> DALI, 0.1% Dimming                                                                 |                            |
| <b>Mounting Option</b>                                                              | <b>AX</b> DMX, 100-0% Dimming                                                                |                            |
|                                                                                     | <b>AH</b> Hi-lume 1% EcoSystem, Soft On / Fade to Black Technology, LDE <sup>1</sup>         |                            |
| <b>Wire Harness</b>                                                                 | <b>AH2</b> ELV 1% 2-wire (Forward and Reverse Phase) <sup>8</sup>                            |                            |
| <b>00</b> Zero Canopy                                                               |                                                                                              |                            |
| <b>0B</b> Zero Block                                                                | <b>Optimized Power</b>                                                                       |                            |
| <b>2R</b> Small Round Canopy                                                        | Add 'O' to power type example: AEO, ATO...etc. <sup>3</sup>                                  |                            |
| <b>2S</b> Small Square Canopy                                                       | <b>VodeNODE</b>                                                                              |                            |
| <b>4R</b> Large Round Canopy                                                        | Add 'N' to power type for Flexible 1 to 1 Power                                              |                            |
| <b>4S</b> Large Square Canopy                                                       | Add 'ON' to power type for Optimized Power example: AEN, ATN, AEON, ADON...etc. <sup>4</sup> |                            |
|                                                                                     | <b>ZZ</b> Other (please specify)                                                             |                            |
|                                                                                     | See <b>Power Guide</b> for driver features & limitations.                                    |                            |

| Emergency Power                                  | LED Type                           | Lumen Output                                              | Color Temperature                 | Optics                                | Sensors                                 |
|--------------------------------------------------|------------------------------------|-----------------------------------------------------------|-----------------------------------|---------------------------------------|-----------------------------------------|
| <b>0</b> No Emergency Power                      | <b>Z</b> Zipper Board              | <b>LO</b> Low Output                                      | <b>90+</b> CRI                    | <b>Zipper Board (Z)</b>               | <b>0</b> None                           |
| <b>ZZ</b> Emergency Power (specify requirements) | <b>B</b> Button Board <sup>5</sup> | <b>SO</b> Standard Output                                 | <b>27</b> 2700K                   | <b>WB</b> White Baffle with EdgeSoft™ | <b>ZZ</b> Sensor (specify requirements) |
|                                                  |                                    | <b>HO</b> High Output                                     | <b>30</b> 3000K                   | <b>BB</b> Black Baffle with EdgeSoft  |                                         |
|                                                  |                                    | <b>ZZ</b> Other (please specify)                          | <b>35</b> 3500K                   | <b>C1</b> Clear with EdgeSoft         |                                         |
|                                                  |                                    | See <b>IES Files</b> page for details.                    | <b>40</b> 4000K                   | <b>D1</b> Diffuse                     |                                         |
|                                                  |                                    | See <b>Power Guide</b> for driver features & limitations. | <b>ZZ</b> Tunable White Available | <b>Button Board (B)</b>               |                                         |
|                                                  |                                    |                                                           | See <b>Guide</b> for details.     | <b>19</b> 19° x 48° Oval              |                                         |
|                                                  |                                    |                                                           |                                   | <b>36</b> 36° Medium                  |                                         |

**NOTES & LIMITATIONS**

- <sup>1</sup> 1.25" arm length is not available with Zero Block (0B).
- <sup>2</sup> For arms 18" and longer, wall-mounted systems include a cable tie-back.
- <sup>3</sup> Optimized Power is not available with Hi-lume 1% EcoSystem (AHO) Power Type.
- <sup>4</sup> VodeNODE enclosure is not available with ELV 1% 2-wire (AH2) Power Type.
- <sup>5</sup> Button Board (B) is not available with 90 CRI.
- <sup>6</sup> 18/3 Cord and Plug only available with Remote Power (RP).
- <sup>7</sup> Chicago Plenum not applicable for wall arm mounting.
- <sup>8</sup> Lengths of 24" and shorter are not supported due to driver limitations. Daisy chaining multiple fixtures to achieve minimum load is permitted but may introduce installation complexity—consult factory for layout guidance.
- <sup>9</sup> Dual Hub comes with a powered and non-powered side. Refer to installation instructions for orientation restrictions.

| Finish                           | Options                                      |
|----------------------------------|----------------------------------------------|
| <b>AL</b> Clear Anodized         | <b>0</b> None                                |
| <b>WH</b> White Powder Coat      | <b>9</b> 9' 18/3 Cord and Plug <sup>6</sup>  |
| <b>BL</b> Black Anodized         | <b>CPP</b> Chicago Plenum Power <sup>7</sup> |
| <b>ZZ</b> Other (please specify) |                                              |


Standard 5 Year Limited Warranty. See details [here](#). Contact factory for options on Limited Warranties up to 20 years.

Listed to UL standards for damp location by a Nationally Recognized Testing Laboratory (NRTL) recognized by OSHA. Certain limitations exist for each Certification. Contact factory for verification.



# Applications

## Interior Corporate, Retail, and Display



HBO Studio, Seattle, WA



University of Pennsylvania, Philadelphia, PA

Sustainability & Certifications

**DECLARE**

**International Living Future Institute (ILFI)**



All Vode Lighting linear light fixtures proudly carry the Red List Approved designation.

**Vode Adaptive Architectural Lighting Systems**  
**Vode Lighting LLC**

**Final Assembly:** Sonoma, California, US  
**Life Expectancy:** 10+ Year(s)  
**End of Life Options:** Recyclable (100%)

**Ingredients:**

Steel; Anodized Aluminum (6063-T5 Alloy); Small Electrical Component (RoHS); Copper; **Fluorinated Ethylene Propylene (masterbatch)**; Polymethyl methacrylate (PMMA); Stainless Steel; Polyoxymethylene Copolymer (POM); Styrene-butadiene polymer, hydrogenated; Poly(methyl methacrylate/butyl acrylate/styrene) (PMMA/BA/S); Styrene/butadiene copolymer; Distillates; Polypropylene; Calcium carbonate; Polycarbonate; EVA Copolymer; Methyl methacrylate (MMA); Polyphenylene Oxide; Brass; Tin, Organic

**Living Building Challenge Criteria:** Compliant

**I-13 Red List:**

LBC Red List Free      % Disclosed: 100% at 100ppm  
 LBC Red List Approved      VOC Content: Not Applicable  
 Declared

**I-10 Interior Performance:** Not Applicable  
**I-14 Responsible Sourcing:** Not Applicable

VDE-0001  
 EXP. 01 FEB 2026  
 Original Issue Date: 2018

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY  
 INTERNATIONAL LIVING FUTURE INSTITUTE™ [living-future.org/declare](http://living-future.org/declare)

Click here to learn more: [International Living Future Institute](http://International Living Future Institute)

**TM65NA**

**CIBSE & ASHRAE on Embodied Carbon**

Vode recognizes TM65NA as the highest standard for understanding the embodied carbon of our fixtures.

Developed with ASHRAE, it adapts CIBSE's TM65 for North America, ensuring accurate regional assessments. It must be used alongside TM65 and follows TM65LA's framework.

**System:** 107 | WingRail | Ceiling Wall Arm  
**Embodied Carbon (kg CO<sub>2</sub>e):** 47.02\*

\***Note:** Embodied Carbon, expressed in kilograms of CO<sub>2</sub>e is calculated using a 48" fixture and includes the LED driver.



Click here to learn more [CIBSE, ASHRAE](#).

**BAA X BABA**

**Buy American Act / Build America & Buy America Act Compliance**

Vode is dedicated to supporting domestic manufacturing and ensuring compliance with BAA and BABA requirements.

Given the complexity of our products, we recommend reaching out to [vodecares@vode.com](mailto:vodecares@vode.com) for confirmation regarding compliance for your specific project.



Click here to learn more: [US Department of Commerce](http://US Department of Commerce)


## Structure

|                       |                                                                                                                 |
|-----------------------|-----------------------------------------------------------------------------------------------------------------|
| Rail Lengths          | 24" (610mm) - 72" (1829mm). Modified lengths available. See <a href="#">Rail Length Chart</a> for more details. |
| Rail Dimensions       | 1.14" (29mm) x 2.12" (54mm) x length.                                                                           |
| Construction          | Extruded and machined 6063 aluminum.                                                                            |
| Mounting              | Ceiling or wall mount to jbox or driver housing.                                                                |
| Arm Length            | 1.25" (32mm) – 24" (610mm). Non-standard arm lengths available.                                                 |
| System Run Length     | 24" (610mm). Unlimited maximum.                                                                                 |
| Operating Temperature | 32°F to 104°F (0°C to 40°C).                                                                                    |
| Humidity              | 0-85%, non-condensing.                                                                                          |
| System Weight         | 1.04 lbs per ft (0.47kg per 305mm) Power supply and housing not included.                                       |


## Materials

|                                   |                                                                                                              |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------|
| LED Board Construction            | Aluminum core PCB, black LCP connectors, RoHS compliant.                                                     |
| Lens                              | High-impact extruded acrylic glass (PMMA).                                                                   |
| Baffle                            | 6063 Aluminum, RoHS compliant painted finish.                                                                |
| Button Optics                     | High-impact cast acrylic glass (PMMA), polycarbonate (PC) holder.                                            |
| Power Cable                       | Ø4mm, 18/2 AWG, Plenum (CMP) rated semi-rigid PVC or FEP, flame tested UL-910 (PVC free in 2020).            |
| Cable Connectors                  | Unfilled black nylon, rated UL 94 V-0, halogen free, PVC or FEP overmold, RoHS compliant (PVC free in 2020). |
| Remote Linear Power Housing (RLP) | 20.7" x 2.375" x 2.53", 0.054" formed Galvanized Steel.                                                      |
| Remote Brick Power Housing (RBP)  | 4.32" x 3.37" x .078" Galvanized Steel mounting plate.                                                       |


## Dimensions



## Mounting Options



## Layout




Corner and Shapes Available (Square, Rectangle, L-Shape, U-Shape, ZigZag) [See Guide](#) for details.

## Power and Controls

|                  |                                                                                                                                                  |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Type       | Class 2 (<60V output) constant current driver.                                                                                                   |
| Dimming Controls | Dimming (0.1%, 1%), 0-10V, DALI, DMX, Hi-lume 1% are available. <a href="#">See Power Guide</a> for details.                                     |
| Input Voltage    | 120V - 277V, 50/60hz.                                                                                                                            |
| Power Location   | Integral or remote power. Maximum remote distance up to 100' (30.5m) depending on driver selection. <a href="#">See Power Guide</a> for details. |


Vode power locations fall into two categories: integral and remote. Remote power is locating the power supply away from the fixture. Remote power comes in two housing styles: brick style and linear style. Consult [Power Guide](#) to determine which type you will receive. Integral power is locating the power supply into the lighting fixture or mounting.

### Remote Brick Power Housing




Supplied for some remote power applications. One remote power supply housing is supplied for each rail. Provided driver mounting plate fits standard 4" metal, square J-Boxes with a minimum volume of 21 in<sup>3</sup> (J-Box not provided). See [Tech Sheet](#) for details.

### Remote Linear Power Housing




One remote power supply housing is supplied with each power supply. All Vode linear remote drivers come in a 0.054" (0.8mm) formed galvanized steel power supply housing with five (5) knockouts: (4) 1-1/8", (1) 7/8" and (1) 9/16". Accommodates standard linear power supplies. See [Tech Sheet](#) for details.

### Integral Power



Houses integral power supply. Direct conduit feed recommended. Housing mounts to standard North America 4" j-box. Mounts to most surfaces. Blocking recommended at all arm junctions. See [Tech Sheet](#) for details.

### Wire Harness




Wire harness connects driver to rail section. Lengths of 10' (3.0m) & 25' (7.6m) with snap-lock connectors for quick and easy installation. Multiple harnesses may be combined for lengths up to 100' (30.5m). See [Tech Sheet](#) for details.

## Power and Controls

### Flexible 1 to 1 power


For Flexible 1 to 1 Power, Vode supplies one single output driver per fixture, allowing each fixture to be controlled independently. Direct/Indirect fixtures are supplied with two single output drivers, allowing the direct and indirect lighting to be controlled independently. Consult [Power Guide](#) to determine which type you will receive.



### Optimized Power

To optimize power, Vode configures specifications with drivers that have 2 or 4 outputs. Depending on system configurations and power requirements, up to 4 fixtures can be powered from a 4-output driver. Consult [Power Guide](#) to determine which type you will receive.

IMPORTANT: Each fixture will still require individual wire harnesses, as shown below.




Note: Drawings not to scale, for reference only.

## Performance | Zipper Board Optics

Zipper Board Optics design has 72 diodes per foot (305mm).

### White Baffle with EdgeSoft (WB)



L80 >60,000 hours


90 CRI (90min., 96 avg.)

| Low Output (LO)            | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 79    | 82    | 83    | 84    |
| Lumens per foot (305mm)    | 271   | 280   | 285   | 288   |
| Watts per foot (305mm)     | 3.5   | 3.5   | 3.5   | 3.5   |

| Standard Output (SO)       | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 91    | 94    | 96    | 97    |
| Lumens per foot (305mm)    | 542   | 560   | 571   | 577   |
| Watts per foot (305mm)     | 6.0   | 6.0   | 6.0   | 6.0   |

| High Output (HO)           | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 84    | 87    | 89    | 90    |
| Lumens per foot (305mm)    | 1031  | 1063  | 1085  | 1096  |
| Watts per foot (305mm)     | 12.3  | 12.3  | 12.3  | 12.3  |

### Black Baffle with EdgeSoft (BB)



L80 >60,000 hours

90 CRI (90min., 96 avg.)

| Low Output (LO)            | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 50    | 51    | 52    | 53    |
| Lumens per foot (305mm)    | 170   | 175   | 179   | 180   |
| Watts per foot (305mm)     | 3.5   | 3.5   | 3.5   | 3.5   |


| Standard Output (SO)       | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 57    | 59    | 60    | 61    |
| Lumens per foot (305mm)    | 339   | 350   | 357   | 361   |
| Watts per foot (305mm)     | 6.0   | 6.0   | 6.0   | 6.0   |

| High Output (HO)           | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 53    | 55    | 56    | 56    |
| Lumens per foot (305mm)    | 644   | 665   | 678   | 685   |
| Watts per foot (305mm)     | 12.3  | 12.3  | 12.3  | 12.3  |

## Performance | Zipper Board Optics

Zipper Board Optics design has 72 diodes per foot (305mm).

### Clear with EdgeSoft (C1)



L80 >60,000 hours


**90 CRI (90min., 96 avg.)**

| <b>Low Output (LO)</b>     | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 95    | 98    | 100   | 101   |
| Lumens per foot (305mm)    | 327   | 337   | 344   | 348   |
| Watts per foot (305mm)     | 3.5   | 3.5   | 3.5   | 3.5   |

| <b>Standard Output (SO)</b> | 2700K | 3000K | 3500K | 4000K |
|-----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt  | 109   | 113   | 115   | 116   |
| Lumens per foot (305mm)     | 654   | 675   | 688   | 695   |
| Watts per foot (305mm)      | 6.0   | 6.0   | 6.0   | 6.0   |

| <b>High Output (HO)</b>    | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 102   | 105   | 107   | 108   |
| Lumens per foot (305mm)    | 1243  | 1282  | 1308  | 1321  |
| Watts per foot (305mm)     | 12.3  | 12.3  | 12.3  | 12.3  |

### Diffuse (D1)



L80 is >60,000 hours

**90 CRI (90min., 96 avg.)**

| <b>Low Output (LO)</b>     | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 68    | 70    | 72    | 73    |
| Lumens per foot (305mm)    | 234   | 241   | 246   | 248   |
| Watts per foot (305mm)     | 3.5   | 3.5   | 3.5   | 3.5   |


| <b>Standard Output (SO)</b> | 2700K | 3000K | 3500K | 4000K |
|-----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt  | 78    | 81    | 83    | 83    |
| Lumens per foot (305mm)     | 467   | 482   | 492   | 497   |
| Watts per foot (305mm)      | 6.0   | 6.0   | 6.0   | 6.0   |

| <b>High Output (HO)</b>    | 2700K | 3000K | 3500K | 4000K |
|----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt | 73    | 75    | 77    | 77    |
| Lumens per foot (305mm)    | 888   | 916   | 935   | 944   |
| Watts per foot (305mm)     | 12.3  | 12.3  | 12.3  | 12.3  |

## Performance | Button Board Optics

Button Board Optics design has 72 diodes per foot (305mm).

### 19° x 48° Oval (19)



L80 >70,000 hours


#### 80 CRI (80min., 84 avg.)

| <b>Standard Output (SO)</b> | 2700K | 3000K | 3500K | 4000K |
|-----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt  | 57    | 59    | 62    | 64    |
| Lumens per foot (305mm)     | 420   | 438   | 456   | 474   |
| Watts per foot (305mm)      | 7.3   | 7.3   | 7.3   | 7.3   |

#### High Output (HO)

|                            |      |      |      |      |
|----------------------------|------|------|------|------|
| Efficacy - Lumens per Watt | 50   | 52   | 55   | 57   |
| Lumens per foot (305mm)    | 636  | 662  | 690  | 717  |
| Watts per foot (305mm)     | 12.6 | 12.6 | 12.6 | 12.6 |

### 36° Medium (36)



L80 >70,000 hours

#### 80 CRI (80min., 84 avg.)

| <b>Standard Output (SO)</b> | 2700K | 3000K | 3500K | 4000K |
|-----------------------------|-------|-------|-------|-------|
| Efficacy - Lumens per Watt  | 64    | 67    | 70    | 73    |
| Lumens per foot (305mm)     | 476   | 496   | 516   | 537   |
| Watts per foot (305mm)      | 7.3   | 7.3   | 7.3   | 7.3   |

#### High Output (HO)

|                            |      |      |      |      |
|----------------------------|------|------|------|------|
| Efficacy - Lumens per Watt | 57   | 60   | 63   | 65   |
| Lumens per foot (305mm)    | 724  | 754  | 786  | 817  |
| Watts per foot (305mm)     | 12.6 | 12.6 | 12.6 | 12.6 |

## Patent Marking

---

This website (<https://www.lmpg.com/patents-trademarks>) is provided to satisfy the virtual patent marking provisions of applicable jurisdictions. Some products listed may be covered by additional patents not referenced here. To learn more, visit <https://www.vode.com/about/legal>

## Copyright

---

*Copyright © 2025 Vode Lighting LLC. All rights reserved. Vode, the Vode logo, BoxRail, FlyWing, MicroBaffle, Button Board, Zipper Board, Zero Canopy, Zero Block, VodeNODE and other names are either registered trademarks or trademarks of Vode Lighting LLC in the United States and may be registered in other countries. All other trademarks listed herein belong to their respective owners. Due to ongoing innovation, specification details may change without notice.*